

NETNode2x2W-5RM-175500T



NETNode IP Mesh Radio Robust Mobile Tri-Band

Overview:


Phase 5 is the latest generation of DTC's NETNode IP Mesh Radio family, offering built-in dual HD video encoders and MIMO capability, providing our highest ever data capacities and maximum frequency flexibility. The latest tri-band product offers increased frequency agility with support for high L-band, S-band and C-band, provided by one physical unit.

IP radios can be combined in a fluid self-forming, self-healing mesh network containing up to 144 nodes depending on operating mode. The tri-band radios exchange bidirectional IP data in a single RF channel, or can utilise different frequency channels for the uplink and downlink traffic, thereby, simplifying frequency management in a complex network.

The entire mesh can operate in bandwidths from 1.25MHz to 20MHz, employing DTC's unique COFDM modulation scheme. Multiple Input Multiple Output (MIMO) technology transmits two signals in the same channel, almost doubling the available data capacity, can also be configured in standard Mesh.

Features and Benefits:

- Self-forming, self-healing Mesh architecture
- Ideal for use for wide area coverage & multi-hop, mobile applications such as robotics and city wide infrastructure
- Tri-band capability in L-band (1.7-1.85GHz), S-band (2.2-2.5GHz) and C-band (4.4-4.9GHz)
- 4G IP connectivity for additional backhaul offering beyond mesh
- Low latency IP communication
- Data capacity up to 90Mbps in 20MHz channel bandwidth
- Composite video encoder with 12V external power
- GPS receiver (antenna required)
- Configurable RF bandwidth from 1.25MHz to 20MHz
- Interlink mode for enhanced capability and large scale systems
- 64Gb of on-board storage with store & forward functionality
- Optional AES128/256 encryption (accredited to FIPS140-2 for MeshUltra™ waveforms)
- Mission Commander compatibility



Product Information:

Product Options

NETNode2x2W-5RM-175500T	IP Mesh Phase 5 Robust Mobile L/S/C Triband 2x2W
NETNode2x2W-5RM-175500T-NAN	IP Mesh Phase 5 Robust Mobile L/S/C Triband 2x2W no composite video input

Product Includes

CA2585	Mic/head and control/debug screened cable
CA3229	Screened power/Ethernet cable
CA3256	Short bananas to XLR power cable

Accessory Options (sold separately)

AP000481	UK IEC power supply cable for use with CA0649
AP001483	US IEC power supply cable for use with CA0649
AP004634	EU IEC power supply cable for use with CA0649
AP007192	AU IEC power supply cable for use with CA0649
AP009259	IP55 water resistant enclosure for use with CA0649
AP009562	Antenna GPS/GLONASS, 1.575-1.6GHz, SMA
CA0649	12VDC power supply unit for use with CA3229
CA3254	5m XLR to XLR extension for use with CA3229
CA3255	10m XLR to XLR extension for use with CA3229
CA3259	Video input and DC power output cable
CA3606	Mic/headphone and RS232/RS485 data cable
MW4044	Pelicans case to house NETNode2x2W-5RMT kit (contact DTC)
*MISCRTAC	Mission Commander Tactical application for desktop or tablet
*MCS	Mission Commander Strategic advanced client/server application
NETR-MB	NETNode Robust mounting bracket kit
SOL8SDI	HDMI or composite video to SDI converter

* Refer to separate datasheets

NETNode2x2W-5RM-175500T

NETNode IP Mesh Radio Robust Mobile Tri-Band

Technical Specification:

IO

COFDM RF interfaces	N-Type x 4 (2 x Tx/Rx, 2 x Rx)
GPS antenna interface	SMA
Power and Ethernet (Eth0)	6-way Amphenol 38999 series 3
Ethernet (Eth1)	RJ45
Config & data	22-way Amphenol 38999 series 3
Composite video & power	4-way Amphenol 62GB
SDI/HD-SDI	BNC 75Ω female
USB	Type A

Typical Range

NLOS light urban	1400m †
LOS (e.g. ground to air)	106km †

† Dependent on antenna height and gain

RF Interfaces

Antenna A	Channel 1 receive only
Antenna B	Channel 1 switched transmit/receive
Antenna C	Channel 2 receive only
Antenna D	Channel 2 switched transmit/receive

RF and Modulation

Tuning step size	125kHz step
Output power	+33dBm per channel in 0.25dB step (4W total)
Bandwidth in MHz (dependent on operating mode)	1.25, 1.5, 1.75, 2.5, 3.0, 3.5, 4.0, 5.0, 6.0, 7.0, 8.0, 10.0, 12.0, 14.0, 16.0, 20.0
Mesh capacity	Up to 87Mbps MIMO, 17Mbps standard Mesh
Modulation	COFDM 360 carrier modulation
Carrier modulation	BPSK/QPSK/16QAM/64QAM (adaptive)
FEC rate	FEC 1/2, FEC 2/3 (adaptive)
Receive diversity	Maximum ratio combining
Receive sensitivity	-98dBm (BW 2.5MHz / QPSK 1/2)
Receive input level	+20dBm max.

IP Interface

Primary and secondary Ethernet electrical	100/1000Base-T Ethernet
IP address allocation	DHCP dynamic IP addressing/static IP

Streaming

Format	UDP multicast/unicast RTSP/RTP/UDP multicast/unicast
MJPEG	TCP/HTTP

Video

Video input	Two video streams Max total throughput of 1920x1080p30
SDI input formats	1920x1080i 60/59.94/50Hz 1920x1080p 30/29.97/25/24/23.97Hz 1920x1080psf 30/29.97/25/24/23.97Hz 1280x720p 60/59.94/50Hz 720x576i 50Hz or 720x480i 59.94Hz
Composite input formats	PAL NTSC
H.264 compression	AVC / H.264 / MPEG-4 Part 10 High profile level 4.0
Coding options	Horizontal scaling of 3/4, 2/3, 1/2, 1/4 Vertical scaling of 1/2, 1/4 Sub-frame rate of 1/2, 1/4, 1/8, 1/24
Encoder delay	1s to 10ms (mode dependent)
Encoder bitrates	0.25Mbps to 32Mbps

Audio

Digital audio input	SD/HD-SDI digital stereo pair
Sample rate	16kHz-48kHz
Coding modes	4 channels stereo or mono MPEG Audio Layer 1 64-448kbps MPEG Audio Layer 2 32-384kbps MPEG Audio Layer 3 8-256kbps
Talkback audio input	Microphone level/headphone output
Compression	G726 32kbit audio 8kHz sampling and mute
Input level (600Ω impedance)	0.25mV to 1.14V RMS
Output level	32mW RMS max into a 16Ω load

Store and Forward Options

Storage format	SD card interface (Secure Digital card) - not user accessible
Record options	Continuous or triggered
Files download	From web browser interface/RTSP
Video and audio clip size	Thirty seconds

Encryption

Standard	DES
Licensed	AES128/256 (subject to export control)

GPS

Built in GPS receiver	Garmin GPS-15xH-W
-----------------------	-------------------

NETNode2x2W-5RM-175500T

NETNode IP Mesh Radio Robust Mobile Tri-Band

Technical Specification (cont.):

Data Interface

RS232/RS485 bi-directional data (shared with user camera control)	1k2 to 115k2 baud switchable with UDP and TCP routing protocol
---	--

Camera Interface

User camera type	One HD-SDI or SD-SDI One PAL or NTSC
User camera control	Mission Commander PC application using VISCA, PELCOD or PELCOP User supplied desk controller (requires RS232/RS485 interface)

Triggers

Trigger source	Video motion detection Brightness
Trigger action	Enable Mesh Record

Control

Local control	LEDs power and Mesh status
Remote control	Web user interface Mission Commander

Physical

Sealing	IP66 minimum
Dimensions	H 160mm, W 160mm, D 70mm
Weight	2.5kg approx.
Mounting options base unit	Through hole screws
Mounting options base plate	Post mounting kit

Power

DC input	10-18V
Power consumed	25W RMS @13V 25% data occupancy 55W RMS @13V 100% data occupancy
Inrush current (power up)	45A @13V
Inrush current (TX cycle)	8A @13V

Environment

Temperature range	-20°C to +50°C
-------------------	----------------

Frequencies

175500	L-band (1.70-1.85GHz), S-band (2.20-2.50GHz), C-band (4.40-4.90GHz)
--------	---

Software License Code

Silver (included)	SIMO Mesh, MIMO Mesh, Multi Mesh, Ultra-Low Bandwidth, Recording, Streaming, DES Encryption
Gold	Silver plus SD H.264 Encoder, Interference Avoidance
Platinum	Gold plus HD H.264 Encoder, Low Bitrate Encoding, Point to Multipoint, Ranging
IAS-NETNode2x2W-5RMT	Interference Avoidance Scheme
L2BRIDGE-NETNode2x2W-5RMT	Transparent L2 Bridging Mode
LOWBIT-NETNode2x2W-5RMT	Low Bitrate Video Encoding
P2MP-NETNode2x2W-5RMT	Point-to-Multipoint
SNAPSHOTS-NETNode2x2W-5RMT	Triggered JPEG stills with timestamps
*AES128	AES128 Cryptography Licence
*AES256	AES256 & AES128 Cryptography Licence

* Accredited to FIPS140-2 for MeshUltra™ waveforms

Encrypted products are subject to regulatory export controls

For further information contact your Sales Account Manager, one of our Regional Sales Offices, or email solent.info@domotactical.com

AMERICA
T: +1 571 563 7077

UK
T: +44 1489 566 750

DENMARK
T: +45 8791 8100

UAE
T: +971 0 44 53 72 01

SINGAPORE
T: +65 6339 0508

AUSTRALIA
T: +61 8 8305 0311